

# Multiprogramming on physical memory

- **Makes it hard to allocate space contiguously**
  - Convenient for stack, large data structures, etc.
- **Need fault isolation between processes**
  - Someone else testing tcpproxy on your machine...
- **Processes can consume more than available memory**
  - Dormant processes (waiting for event) still have core images

## **Solution: Address Spaces**

- **Give each program its own address space**
- **Only “privileged” software can manipulate mappings**
- **Isolation is natural**
  - Can't even name other proc's memory

# Alternatives

- **Segmentation**

- Part of each memory reference implicit in segment register  
 $\text{segreg} \leftarrow \langle \text{offset}, \text{limit} \rangle$
- By loading segment register code can be relocated
- Can enforce protection by restricting segment register loads

- **Language-level protection (Java)**

- Single address space for different modules
- Language enforces isolation

- **Software fault isolation**

- Instrument compiler output
- Checks before every store operation prevents modules from trashing each other

# Paging

- **Divide memory up into small “pages”**
- **Map virtual pages to physical pages**
  - Each process has separate mapping
- **Allow OS to gain control on certain operations**
  - Read-only pages trap to OS on write
  - Invalid pages trap to OS on write
  - OS can change mapping and resume application
- **Other features sometimes found:**
  - Hardware can set “dirty” bit
  - Control caching of page

## Example: Paging on PDP-11

- 64K virtual memory, 8K pages
- 8 Instruction page translations, 8 Data page translations
- Swap 16 machine registers on each context switch

## Example: VAX

- **Virtual memory partitioned**
  - First 2 Gigs for applications
  - Last 2 Gigs for OS—mapped same in all address spaces
  - One page table for system memory, one for each process
- **Each user page table is 8 Megabytes**
  - 512-byte pages, 4 bytes/translation,  
1 Gig for application (not counting stack)
- **User page tables stored in paged kernel memory**
  - No need for 8 physical Megs/proc. only virtual


## Example: MIPS

- **Hardware has 64-entry TLB**
  - References to addresses not in TLB trap to kernel
- **Each TLB entry has the following fields:**

Virtual page, Pid, Page frame, NC, D, V, Global
- **Kernel itself unpaged**
  - All of physical memory contiguously mapped in high VM
  - Kernel uses these pseudo-physical addresses
- **User TLB fault handler very efficient**
  - Two hardware registers reserved for it
  - utlb miss handler can itself fault—allow paged page tables

## Example: Paging on x86

- **Page table: 1024 32-bit translations for 4 Megs of Virtual mem**
- **Page directory: 1024 pointers to page tables**
- **%cr3—page table base register**
- **%cr0—bits enable protection and paging**
- **INVLPG – tell hardware page table modified**



\*32 bits aligned onto a 4-KByte boundary

## Page-Table Entry (4-KByte Page)

31

12 11    9 8 7 6 5 4 3 2 1 0



Available for system programmer's use

Global Page

Page Table Attribute Index

Dirty

Accessed


Cache Disabled

Write-Through

User/Supervisor

Read/Write

Present



## 64-bit address spaces

- **Some machines have 64-bit virtual address spaces**
- **Makes hierarchical page tables inconvenient**
  - E.g., might need to walk five levels of table on page fault!
- **Solution: Hashed page tables**
  - Store Virtual → Physical translations in hash table
  - Table size proportional to physical memory
- **Precludes hardware table walking**
  - Not a problem with large enough software-controlled TLB

# OS effects on application performance

- **Page replacement**

- Optimal – Least soon to be used (impossible)
- Least recently used (hard to implement)
- Random
- Not recently used

- **Direct-mapped physical caches**

- Virtual → Physical mapping can affect performance
- Applications can conflict with each other or themselves
- Scientific applications benefit if consecutive virtual pages to not conflict in the cache
- Many other applications do better with random mapping

## Paging in day-to-day use

- Demand paging
- Shared libraries
- Shared memory
- Copy-on-write (fork, mmap, etc.)

# VM system calls

- `void *mmap (void *addr, size_t len, int prot, int flags, int fd, off_t offset)`
  - `prot`: OR of `PROT_EXEC`, `PROT_READ`, `PROT_WRITE`, `PROT_NONE`
  - `flags`: `shared/private`, ...
- `int munmap(void *addr, size_t len)`
  - Removes memory-mapped object
- `int mprotect(void *addr, size_t len, int prot)`
  - Changes protection on pages to or of `PROT...`
- `int mincore(void *addr, size_t len, char *vec)`
  - Returns in `vec` which pages present

# Catching page faults

```
struct sigaction {
    union {
        /* signal handler */
        void (*sa_handler)(int);
        void (*sa_sigaction)(int, siginfo_t *, void *);
    };
    sigset_t sa_mask;    /* signal mask to apply */
    int sa_flags;
};

int sigaction (int sig, const struct sigaction *act,
              struct sigaction *oact)
```

- **Can specify function to run on SIGSEGV**

## Example: OpenBSD/i386 siginfo

```
struct sigcontext {
    int sc_gs; int sc_fs; int sc_es; int sc_ds;
    int sc_edi; int sc_esi; int sc_ebp; int sc_ebx;
    int sc_edx; int sc_ecx; int sc_eax;

    int sc_eip; int sc_cs; /* instruction pointer */
    int sc_eflags; /* condition codes, etc. */
    int sc_esp; int sc_ss; /* stack pointer */

    int sc_onstack; /* sigstack state to restore */
    int sc_mask; /* signal mask to restore */


    int sc_trapno;
    int sc_err;
};
```

# Advantages/disadvantages of paging

- **What happens to user/kernel crossings?**
  - More crossings into kernel
  - Pointers in syscall arguments must be checked
- **What happens to IPC?**
  - Must change hardware address space
  - Increases TLB misses
  - Context switch flushes TLB entirely on x86  
(But not on MIPS... Why?)

## Example: 4.4 BSD VM system

- **Each process has a *vm\_space* structure containing**
  - *vm\_map* – machine-independent virtual address space
  - *vm\_pmap* – machine-dependent data structures
  - statistics – e.g. for syscalls like *getrusage* ()
- ***vm\_map* is a linked list of *vm\_map\_entry* structs**
  - *vm\_map\_entry* covers contiguous virtual memory
  - points to *vm\_object* struct
- ***vm\_object* is source of data**
  - e.g. vnode object for memory mapped file
  - points to list of *vm\_page* structs (one per mapped page)
  - *shadow objects* point to other objects for copy on write



## **Pmap (machine-dependent) layer**

- **Pmap layer holds architecture-specific VM code**
- **VM layer invokes pmap layer**
  - On page faults to install mappings
  - To protect or unmap pages
  - To ask for dirty/accessed bits
- **Pmap layer is lazy and can discard mappings**
  - No need to notify VM layer
  - Process will fault and VM layer must reinstall mapping
- **Pmap handles restrictions imposed by cache**

# Example uses

- ***vm\_map\_entry* structs for a process**
  - r/o text segment → file object
  - r/w data segment → shadow object → file object
  - r/w stack → anonymous object
- **New *vm\_map\_entry* objects after a fork:**
  - Share text segment directly (read-only)
  - Share data through two new shadow objects  
(must share pre-fork but not post fork changes)
  - Share stack through two new shadow objects
- **Must discard/collapse superfluous shadows**
  - E.g., when child process exits

# What happens on a fault?

- **Traverse *vm\_map\_entry* list to get appropriate entry**
  - No entry? Protection violation? Send process a SIGSEGV
- **Traverse list of [shadow] objects**
- **For each object, traverse *vm\_page* structs**
- **Found a *vm\_page* for this object?**
  - If first *vm\_object* in chain, map page
  - If read fault, install page read only
  - Else if write fault, install copy of page
- **Else get page from object**
  - Page in from file, zero-fill new page, etc.